

## Bronze Globe Valve (Transformer)

## Class 2 • S I B • Rising Stem • Flanged Ends • Locking Rod





### Product no. 122200IL


### Size Range:

1/2 through 4 inches

Max. temperature limit is 450°F (232°C)

# Working Pressures / Temperature Rating:

50 lbs/in² at 250 °F Transformer Oil 3.5 bar at 121 °C Transformer Oil 650 kPa at 121 °C Transformer Oil



### **Features**

- · Rising Stem
- · Screwed Bonnet
- Flanged Ends are plain faces with two v-shaped concenttric grooves between the port and bolt holes.
- PTFE Gland Packing and Seat Disc
- Integral Bronze Seat
- · Powder Coated Alumnium Handwheel
- Recommended for Transformer Oil
- Powder Coated Locking Rod for Padlock
- Disc Holder Spun with stem up to size 2" and above retained by a threaded ring For more details please contact: export@oswalvalve.com

Above size 4" also avaliable on request

TESTING HYDROSTATIC: BODY: 24 Kg/Cm<sup>2</sup>

SEAT : 16 Kg/Cm<sup>2</sup>

## **Principal Parts & Materials**

Part	Material	IS
Body	Bronze	318 LTB 2
Bonnet	Bronze	318 LTB 2
Disc	Bronze	318 LTB 2
Stem	Brass	319 Type II

### **Dimensions and Weights**

Millimeters - Kilograms

DN	1/2" 15	3/4" 20	1" 25	1 1/4" 32	1 1/2" 40	2" 50	2 1/2" 65	3" 80	4" 100
Α	75	85	95	100	120	145	165	185	216
В	90	110	120	140	155	170	210	225	280
С	60	65	75	75	95	110	125	125	175
WTS.	1.30	1.60	2.50	3.80	5.00	6.20	10.30	14.50	26.30